

1 **SECTION 9-34, PAVEMENT MARKING MATERIAL**

2 **April 3, 2006**

3 **9-34.2 Paint**

4 This section is revised to read:

5

6 White and yellow paint shall comply with the specifications for high volatile organic
7 compound (VOC) solvent based paint, low VOC solvent based paint or low VOC
8 waterborne paint. Blue paint for "Access Parking Space Symbol with Background" shall
9 be chosen from a WSDOT QPL listed Manufacturer. The blue color shall match Fed
10 Standard 595, color 15090 and the tolerance of variation shall match that shown in the
11 FHWA "Highway Blue Color Tolerance Chart."

12

13 **9-34.3 Plastic**

14 This section is revised to read:

15

16 White and yellow plastic pavement marking materials shall comply with the
17 specifications for:

18

19 Type A – Liquid hot applied thermoplastic

20 Type B – Pre-formed fused thermoplastic

21 Type C – Cold applied pre-formed tape

22 Type D – Liquid cold applied methyl methacrylate

23

24 Blue plastic pavement marking material for "Access Parking Space Symbol with
25 Background" shall be chosen from a WSDOT QPL listed Manufacturer. The blue color
26 shall match Fed Standard 595, color 15090 and the tolerance of variation shall match
27 that shown in the FHWA "Highway Blue Color Tolerance Chart."

28

29 **9-34.4 Glass Beads**

30 In the first sentence the reference to AASHTO M 247-81, Type 1 is revised to AASHTO M
31 247, Type 1.